



PERLVLIIES

Product description

- Material** Perlvlies is a pre-painted glass veil with micro glass beads which form modern structures. Pervlies consists of mineral materials.
- Use** Perlvlies offer a wide range of individual design compared to classical glass fibre wall-coverings. It is best used in high traffic areas or to decorate a feature wall.
- Properties**
- Tear-resistant, dimensionally stable, bridges cracks
 - Paintable with metallic, opaque paints or glaze for unique effects
 - 3D effect and, after painting, a changing 2-colour effect
 - Rot resistant
 - Free of PVC and plasticizers
- Certificates**
- Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
 - Oeko Tex® Standard 100
 - Contains no allergenic substances
 - A+ (VOC)

Roll size and packaging

Article	Roll size	Weight approx.	Repeat
30001 013	1,00 x 13,00 m	277 g/m ²	16 cm
30002 013	1,00 x 13,00 m	452 g/m ²	1 cm
30003 013	1,00 x 13,00 m	440 g/m ²	--
30004 013	1,00 x 13,00 m	467 g/m ²	2,5 cm
30005 013	1,00 x 13,00 m	332 g/m ²	1,5 cm
30006 013	1,00 x 13,00 m	515 g/m ²	--
30007 013	1,00 x 13,00 m	355 g/m ²	64 cm
30008 013	1,00 x 13,00 m	247 g/m ²	--
30009 013	1,00 x 13,00 m	300 g/m ²	32 cm
30010 013	1,00 x 13,00 m	375 g/m ²	64 cm
30011 013	1,00 x 13,00 m	275 g/m ²	32 cm
30012 013	1,00 x 13,00 m	245 g/m ²	16 cm
30013 013	1,00 x 13,00 m	265 g/m ²	64 cm

Packaging: box: 1 roll, pallet: 24 rolls



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical
data sheet

LECO
so simple. so good.

PERLVLIIES

Instructions of use

First step

Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material, pattern repeat and equal batch numbers is required. Claims after usage will not be accepted.

Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

Hanging

Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.

Cut wallpaper length to according height incl. 5 - 10 cm extra material. Beware of the pattern repeat. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

Painting

Prior to painting, wallpaper must be swept with a soft brush. Once dry, the wallcovering must be painted with an adequate paint like (metallic) dispersion, latex or acrylic paint according to DIN 13300 or with glaze. For a special brilliance use metallic dispersion. Please observe manufacturer's instructions. For further recommendations contact your local distributor.

Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

03/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

LECO-Werke Lechteck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de