



Technical  
data sheet



# LECO Magnetic Wall

## Product description

**Material** LECO Magnetic Wall s is a multi-layered wallcovering consisting of a pre-coated glass veil, an ironcontaining magnetic coating and a nonwoven as backing.

**Use** Ideal for offices, conference rooms, schools, kindergartens, doctor's surgeries, airports, exhibition booths or in private homes. Create fast and easy in your preferred size presentation, working or playing surfaces.

**Properties**

- High quality
- Optimised seam behaviour
- Excellent embedding of magnetic coating
- Easy cutting with cutter knife
- Low weight
- Easy, clean and fast to work
- No shielding effect
- Non-conductive
- No impairment of wireless LAN and mobile phones
- Free of solvents and plasticisers

**Certificates**

- Complies with CE DIN EN 15102
- Flame retardant in accordance with DIN EN 13501-1 (C-s1, d0)
- Oeko Tex® Standard 100
- Contains no allergenic substances
- A+ (VOC)

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	38700 026	1,00 x 2,60 m	1.100 g/m <sup>2</sup>	1 roll	24 rolls
	38700 052	1,00 x 5,20 m	1.100 g/m <sup>2</sup>	1 roll	24 rolls
	38700 104	1,00 x 10,40 m	1.100 g/m <sup>2</sup>	1 roll	24 rolls

**Magnet recommendation** Neodymium-Magnets are recommended. Thanks to their high adhesive force several sheets of paper can be easily attached.

03/2024



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical  
data sheet

**LECO**  
so simple. so good.

# LECO Magnetic Wall

## Instructions of use

### First step

Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material and equal batch numbers is required. Claims after usage will not be accepted.

### Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

### Hanging

Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.

Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

### Painting

Once dry, the wallcovering must be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. You can coat the LECO Magnetic Wall with blackboard paint or whiteboard paint for maximum creativity.

### Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

03/2024

<b>CE</b>
<b>18</b>
LECO-Werke Lechtreck GmbH & Co. KG Hollefeldstraße 41 D 48282 Emsdetten
EN 15102: T4 / 5
EN 15102: 2007 - A1: 2011
NB 1508
C>1, d0
www.leco-werke.de



**STANDARD  
100**

09.0.69682  
Hohenstein HTTI



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de