



LECO Magnetic whiteboard

Product description

Material LECO Magnetic whiteboard is a multi-layer nonwoven consisting of a matt whiteboard film, a ferrous magnetic coating and a smooth nonwoven on the reverse side.

Use Ideal for offices, conference rooms, schools, kindergartens, doctor's surgeries, airports, exhibition booths or in private homes. Create fast and easy in your preferred size presentation, working or playing surfaces. The scratch-resistant, white magnetic film can be written on any number of times with whiteboard markers without leaving ghosting or shadows behind. Writing can be easily removed with a dry microfibre cloth. The film therefore offers a practical two-in-one solution for creating high-quality, multifunctional communication surfaces in just one step.

- Properties**
- High quality
 - Optimised seam behaviour
 - Excellent embedding of magnetic coating
 - Easy cutting with cutter knife
 - Low weight
 - Easy, clean and fast to work
 - No shielding effect
 - Non-conductive
 - No impairment of wireless LAN and mobile phones
 - Free of solvents and plasticisers

- Certificates**
- Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 13501-1 (C-s1, d0)
 - Oeko Tex® Standard 100
 - Contains no allergenic substances
 - A+ (VOC)

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	38810 026	1,00 x 2,60 m	1.730 g/m ²	1 roll	24 rolls
	38810 052	1,00 x 5,20 m	1.730 g/m ²	1 roll	24 rolls

03/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical
data sheet

LECO

LECO Magnetic whiteboard

Instructions of use

- First step** Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material and equal batch numbers is required. Claims after usage will not be accepted.
- Wall surface** The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.
- Hanging** Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.
- Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.
- Note** The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.
- Magnet recommendation** Neodymium-Magnets are recommended. Thanks to their high adhesive force several sheets of paper can easily be attached.
- The nonwoven can be written on with all commercially available whiteboard markers. For easy removal of writing, a microfibre cloth and glass cleaner must be used. In case of accidental use of unsuitable pens, such as permanent markers, the nonwoven can be cleaned with alcohol or cleaning spirit without leaving any residues.

03/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)