



Technical
data sheet



LECO ISOLE TREND

Product description

Material	LECO ISOLE TREND is a polyester and cellulose non-woven.
Use	In addition to insulation, LECO ISOLE TREND offers a wide range of modern designs. It is particularly recommended where interior insulation and decorative design is required. It stands out through its high functional benefit as a thermal insulator in combination with noble structures.
Properties	<ul style="list-style-type: none"> • Thermal insulation ($\lambda = 0,023$) • Dimensionally stable • Bridges cracks • Covers little irregularities • Trendy design • Expressive thanks to deep embossing • Pre-pigmented • Individual paintings and paint techniques • Free of PVC • Free of glass fibres • Skin friendly
Certificates	<ul style="list-style-type: none"> • Complies with CE DIN EN 15102 • Flame retardant in accordance with DIN EN 13501-1 (C-s1, d0) • Oeko Tex® Standard 100 • Contains no allergenic substances • A+ (VOC) • FSC® Mix

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	51000 010	1,00 x 15,00 m	380 g/m ²	6 rolls	24 rolls
	51003 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51005 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51006 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51009 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51010 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51021 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
	51023 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls

07/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)





Technical
data sheet



LECO ISOLE TREND

51024 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
51025 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
51026 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
51029 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls
51030 060	1,00 x 25,00 m	250 g/m ²	6 rolls	24 rolls

Instructions of use

First step

Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material and equal batch numbers is required. Claims after usage will not be accepted.

Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

Hanging

Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions. Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a spatula or rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

Painting

Once dry, the wallcovering can be used as a wall liner or can be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor.

Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

07/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de