



Technical  
data sheet



# LECO GRILLE

## Product description

<b>Material</b>	LECO Grille is made from carefully selected glass fibres.
<b>Use</b>	LECO Grille reinforces plaster, prevents cracking and can be used on inside and outside walls.
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Easy to apply</li> <li>• Reinforces plaster</li> <li>• Prevents cracking</li> <li>• Rot resistant</li> <li>• Dimensionally stable</li> </ul>
<b>Certificates</b>	<ul style="list-style-type: none"> <li>• Complies with CE DIN EN 15102</li> <li>• Oeko Tex® Standard 100</li> <li>• Contains no allergenic substances</li> <li>• A (VOC)</li> </ul>

<b>Roll size and packaging</b>	<u>Article</u>	<u>Roll size</u>	<u>Weight approx.</u>	<u>Packing unit</u>	<u>Rolls per pallet</u>
	60930 080	1,00 x 50,00 m	160 g/m <sup>2</sup>	6 rolls	24 rolls

## Instructions of use

<b>First step</b>	Please check product prior to hanging. Irregularities in material are characteristic for this product. They do not entitle to claims. Claims after usage will not be accepted.
<b>Hanging</b>	<p>Cut LECO Grille length to according height.</p> <p>Apply a first coat of plaster onto your wall. Work LECO Grille into the wet layer of plaster, using a brush. Finish work applying a second coat of plaster to cover LECO Grille entirely.</p>
<b>Note</b>	The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

07/2024



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)