



# Minerals Performance AQUA

## Product description

**Material** Pre-painted glass veil with pre-pasted back.

**Use** With the Aqua technology, wallcoverings by LECO can be worked time-efficient, cleanly and professionally. The pre-pasted back of the wallcovering is placed in the Aqua machine; it is then pulled through, which activates the paste. No additional adhesive is required.

- Properties**
- Works time-efficient
  - Clean and professional
  - Suitable for contract
  - Water activates the glue
  - For walls and ceilings
  - Dimensionally stable, bridges cracks (hairline and fatigue cracks)
  - Paintable
  - Pre-painted glass veil: only 1 coat of paint necessary → saves paint and time

- Certificates**
- Complies with CE DIN EN 15102
  - Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
  - Oeko Tex® Standard 100
  - Contains no allergenic substances
  - A+ (VOC)

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	61010 080	1,00 x 50,00 m	152 g/m <sup>2</sup>	6 rolls	24 rolls
	61013 080	1,00 x 50,00 m	220 g/m <sup>2</sup>	4 rolls	16 rolls

03/2024



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical  
data sheet



# Minerals Performance AQUA

## Instructions of use

- First step** Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material is required. Claims after usage will not be accepted.
- Wall surface** The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary, treat prior to hanging.
- Hanging** Do not work under 8 °C air/wall temperature. Fill water in the aqua pasting machine. Pull wallcovering through the aqua pasting machine. Cut wallpaper length to according height incl. 5 - 10 cm extra material. Glue is activated within 1 minute. For ceiling hanging, 2 - 3 minutes soaking time required. Apply the wallpaper length to the wall smoothing out air bubbles with a spatula or rubber roller. Butt join following length or overlap and double cut. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.
- Painting** Once dry, the wallcovering can be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor.
- Note** The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

03/2024



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)