



LECOUSTIC GLAS

Product description

Material LECOUSTIC Glas is a pre-painted glass fibre wallcovering combined with a non-woven.

Use LECOUSTIC Glas prevents cold walls, saves energy and optimises room acoustic. It also covers up cracks and small irregularities, is durable and can be painted on several times. Advisable where it is important to reduce noise and energy consumption.

- Properties**
- Thermal insulation:
 $\lambda = 0,030 \text{ W/mK (62100)}, 0,039 \text{ W/mK (62120 + 62150)}$
 - Acoustic absorption
 - Breathable
 - Impact resistant, dimensionally stable, bridges cracks, resistant to abrasion
 - Pre-painted → saves 1 coat of paint
 - Free of PVC, plasticizers and solvents

- Certificates**
- Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 4102 (B.-s1, d0)
 - Oeko Tex® Standard 100
 - Contains no allergenic substances
 - A+ (VOC)

| Roll size and packaging | Article | Roll size | Weight approx. | Packing unit | Rolls per pallet |
|-------------------------|-----------|----------------|----------------------|--------------|------------------|
| | 62100 010 | 1,00 x 12,50 m | 475 g/m ² | 6 rolls | 24 rolls |
| | 62120 010 | 1,00 x 12,50 m | 500 g/m ² | 6 rolls | 24 rolls |
| | 62150 010 | 1,00 x 12,50 m | 500 g/m ² | 6 rolls | 24 rolls |





Technical
data sheet



LECOUSTIC GLAS

Instructions of use

- First step** Please check product prior to hanging. Irregularities in material are characteristic for this product. They do not entitle to claims. A control of the material and equal batch numbers is required. Claims after usage will not be accepted.
- Wall surface** The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.
- Hanging** Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.
- Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.
- Painting** Once dry, the wallcovering must be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300 or with glaze. Please observe manufacturer's instructions. For further recommendations contact your local distributor.
- Note** The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

02/2024



LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten
Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de