



Technical  
data sheet



# LECO Design

## Product description

**Material** LECO Design wallpapers are one-sided embossed polyester and cellulose non-woven.

**Use** LECO Design creates trendy design foundations for individually designed walls and ceilings. It is also suitable for renovation and repair of surfaces which are cracked or at risk of cracking. It covers also small irregularities.

- Properties**
- Easy, clean and quick to apply
  - Breathable
  - Impact resistant
  - Dimensionally stable, bridges cracks (hairline and fatigue cracks)
  - Pre-pigmented
  - Paintable
  - Dry strippable
  - Free of PVC, plasticizers and solvents
  - Free of glass fibres
  - Skin friendly

- Certificates**
- Complies with CE DIN EN 15102
  - Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
  - Oeko Tex® Standard 100
  - Contains no allergenic substances
  - A+ (VOC)
  - FSC® Mix

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	63905 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63906 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63909 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63921 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63924 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63926 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63927 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls
	63928 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	4 rolls	48 rolls

07/2024



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de



Technical data sheet



# LECO Design

## Instructions of use

### First step

Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material, pattern repeat and equal batch numbers is required. Claims after usage will not be accepted.

### Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

### Hanging

Use the non-woven adhesive LECOLLE Universal observing manufacturer's instructions. Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a spatula or rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

### Painting

Once dry, the wallcovering can be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor.

### Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

07/2024

CE
11
LECO-Werke Lechtreck GmbH & Co. KG Hollefeldstraße 41 D-48282 Emsdetten
EN 15102; T4 / 2
EN 15102:2007 + A1:2011
NB 0432
B-s1, d0
www.leco-werke.de



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de