



Technical
data sheet



REVELATION®

Product description

Material Revelation® is a pre-painted glass fibre with flock which forms elegant and expressive structures.

Use Revelation® offers design with all the advantages of a glass fibre wallcovering.

Properties

- Impact resistant, dimensionally stable, bridges cracks
- Velvety appearance
- Patented 2-colour effect
- 3D-effect with only 1 coat of paint
- Free of PVC and plasticizers

Certificates

- Complies with CE DIN EN 15102
- Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
- Oeko Tex® Standard 100
- Contains no allergenic substances
- A+ (VOC)

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	70004 020	1,00 x 15,00 m	155 g/m ²	15 rolls	60 rolls
	70008 020	1,00 x 15,00 m	165 g/m ²	15 rolls	60 rolls
	70009 020	1,00 x 15,00 m	175 g/m ²	15 rolls	60 rolls
	70011 020	1,00 x 15,00 m	170 g/m ²	15 rolls	60 rolls
	70015 020	1,00 x 15,00 m	175 g/m ²	15 rolls	60 rolls
	70016 020	1,00 x 15,00 m	175 g/m ²	15 rolls	60 rolls

03/2024



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical
data sheet

LECO
so simple. so good.

REVELATION®

Instructions of use

First step

Please check product prior to hanging. Despite high quality standards irregularities in material cannot be excluded entirely. Therefore a control of the material, pattern repeat and equal batch numbers is required. Claims after usage will not be accepted.

Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

Hanging

Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.

Cut wallpaper length to according height incl. 5 - 10 cm extra material. Beware of the pattern repeat. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

Painting

Once dry, the wallcovering must be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please ensure that the colour is evenly applied wet-in-wet. Please observe manufacturer's instructions. For further recommendations contact your local distributor.

Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

03/2024

CE
13
LECO-Werke Lechtreck GmbH & Co. KG Hollefeldstraße 41 D-48282 Emsdetten
EN 15102: T4 / 3
EN 15102: 2007 + A1: 2011
NB 0432
B-s1, d0
www.leco-werke.de



**STANDARD
100**
09.0.69682
Hoherstein HTTI



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)