



Technical data sheet



COMPACT PRO

Product description

Material Compact PRO is a white, pre-pigmented polyester and cellulose non-woven. It is particularly soft and very dense.

Use With its even surface, Compact PRO creates clean and breathable substrates for creative painting in the contract sector. It delivers excellent results when applied using the paste-the-wall technique or with a pasting machine and is also very suitable for the airless method.

- Properties**
- Very white and soft
 - Pre-pigmented
 - High opacity
 - Very dense and even surface
 - Very good colour absorption with Individual coating
 - Improved substrate coverage, therefore only one coat is required in most cases
 - Suitable for airless application
 - Reliable result when applied using the paste-the-wall technique or with a pasting machine
 - Hard-wearing, tear-resistant, dimensionally stable and crack-bridging
 - Open to diffusion and moisture-regulating
 - Easy to remove
 - Skin-friendly (glass fibre-free)

- Certificates**
- Oeko Tex® Standard 100
 - Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
 - FSC® Mix
 - A+ (VOC)

- Environmental compatibility & indoor climate**
- free from PVC, solvents, plasticizers, formaldehyde and heavy metals
 - free from substances that are hazardous to the environment or health during disposal

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	80000 060	1,00 x 25,00 m	150 g/m ²	15 rolls	60 rolls
	80000 070	0,75 x 25,00 m	150 g/m ²	4 rolls	120 rolls
	80000 073	0,75 x 50,00 m	150 g/m ²	4 rolls	64 rolls
	80000 074	0,75 x 125,00 m	150 g/m ²	1 roll	30 rolls

06/2025



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



LECO-Werke Lehtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de



Technical data sheet



COMPACT PRO

Instructions of use

First step

Please check product prior to hanging.
Pay attention to the marking on the back, as the fleece is pre-coated on the front.
Claims after usage will not be accepted.

Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

Hanging

Use the non-woven adhesive LECOLLE Universal observing manufacturer's instructions.
Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a spatula or rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

Painting

Once dry, the wallcovering can be used as a wall liner or can be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. In most cases, one coat is sufficient.

Compact PRO is very suitable for airless spraying technology.

Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

06/2025



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de