



Technical  
data sheet



# LECO Glass fibres

## Product description

<b>Material</b>	Mineral wallcoverings made from carefully selected glass fibres.
<b>Use</b>	The durability of glass fibre wallcoverings offers a multitude of options in use. It is best used in high traffic areas and suitable for contract.
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Easy to apply</li> <li>• Impact resistant, dimensionally stable, bridges cracks, resistant to abrasion</li> <li>• Paintable individually</li> <li>• Suitable for all spaces</li> <li>• Rot resistant</li> <li>• Free of PVC, plasticizers and solvents</li> </ul>
<b>Certificates</b>	<ul style="list-style-type: none"> <li>• Complies with CE DIN EN 15102</li> <li>• Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)</li> <li>• Oeko Tex® Standard 100</li> <li>• Contains no allergenic substances</li> <li>• A+ (VOC)</li> </ul>

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	60100 080	1,00 x 50,00 m	135 g/m <sup>2</sup>	9 rolls	36 rolls
	60102 080	1,00 x 50,00 m	135 g/m <sup>2</sup>	8 rolls	32 rolls
	60110 080	1,00 x 50,00 m	125 g/m <sup>2</sup>	6 rolls	24 rolls
	60113 080	1,00 x 50,00 m	110 g/m <sup>2</sup>	6 rolls	24 rolls
	60120 080	1,00 x 50,00 m	170 g/m <sup>2</sup>	8 rolls	32 rolls
	60121 080	1,00 x 50,00 m	160 g/m <sup>2</sup>	6 rolls	24 rolls
	60122 080	1,00 x 50,00 m	120 g/m <sup>2</sup>	6 rolls	24 rolls
	60150 080	1,00 x 50,00 m	140 g/m <sup>2</sup>	6 rolls	24 rolls
	60151 080	1,00 x 50,00 m	140 g/m <sup>2</sup>	6 rolls	24 rolls
	60160 080	1,00 x 50,00 m	175 g/m <sup>2</sup>	5 rolls	20 rolls
	60170 080	1,00 x 50,00 m	170 g/m <sup>2</sup>	6 rolls	24 rolls
	60175 080	1,00 x 50,00 m	165 g/m <sup>2</sup>	6 rolls	24 rolls

07/2025



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical  
data sheet



# LECO Glass fibres

Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
60180 080	1,00 x 50,00 m	180 g/m <sup>2</sup>	6 rolls	24 rolls
60191 080	1,00 x 50,00 m	250 g/m <sup>2</sup>	6 rolls	24 rolls
60195 080	1,00 x 50,00 m	200 g/m <sup>2</sup>	6 rolls	24 rolls
60301 060	1,00 x 25,00 m	185 g/m <sup>2</sup>	12 rolls	48 rolls
60510 080	1,00 x 50,00 m	230 g/m <sup>2</sup>	4 rolls	16 rolls
60520 060	1,00 x 25,00 m	250 g/m <sup>2</sup>	7 rolls	28 rolls
60815 080	1,00 x 50,00 m	110 g/m <sup>2</sup>	9 rolls	36 rolls
60861 080	1,00 x 50,00 m	150 g/m <sup>2</sup>	6 rolls	24 rolls
60871 080	1,00 x 50,00 m	160 g/m <sup>2</sup>	6 rolls	24 rolls
60882 080	1,00 x 50,00 m	170 g/m <sup>2</sup>	6 rolls	24 rolls
60895 080	1,00 x 50,00 m	100 g/m <sup>2</sup>	8 rolls	32 rolls

Pre-painted – saves time and paint:

64100 080	1,00 x 50,00 m	145 g/m <sup>2</sup>	12 rolls	48 rolls
64101 080	1,00 x 50,00 m	145 g/m <sup>2</sup>	8 rolls	32 rolls
64150 080	1,00 x 50,00 m	150 g/m <sup>2</sup>	6 rolls	24 rolls
64151 080	1,00 x 50,00 m	150 g/m <sup>2</sup>	6 rolls	24 rolls
64165 080	1,00 x 50,00 m	195 g/m <sup>2</sup>	3 rolls	12 rolls
64166 080	1,00 x 50,00 m	170 g/m <sup>2</sup>	4 rolls	16 rolls
64180 080	1,00 x 50,00 m	195 g/m <sup>2</sup>	6 rolls	24 rolls
64600 080	1,00 x 50,00 m	150 g/m <sup>2</sup>	9 rolls	36 rolls
64895 080	1,00 x 50,00 m	115 g/m <sup>2</sup>	8 rolls	32 rolls

07/2025



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

LECO-Werke Lechtreck GmbH & Co. KG · Hollefeldstr. 41 · D - 48282 Emsdetten

Tel.: +49 2572 207-0 · walls@leco-werke.de · www.leco-werke.de



Technical  
data sheet



# LECO Glass fibres

## Instructions of use

### First step

Please check product prior to hanging. Irregularities in material are characteristic for this product. They do not entitle to claims. A control of the material and equal batch numbers is required. Claims after usage will not be accepted.

### Wall surface

The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary treat prior to hanging.

### Hanging

We recommend LECOLLE Universal glass fibre adhesive or, for wallcoverings above 200 g/m<sup>2</sup>, LECOLLE Xtra Strong.

Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.

### Painting

Once dry, the wallcovering must be painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor. After drying of first coat of painting, potential uprising fibres have to be sanded.

### Note

The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt please test.

07/2025



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)