



Technical data sheet



LECO Minerals


Product description

- Material** Glass veils are all mineral wallcoverings made from carefully selected glass fibres.
- Use** The durability of glass veils offers a multitude of options in use. It is best used in high traffic areas and suitable for contract. Use glass veil to obtain a uniform wall surface.
- Properties**
- Easy to apply
 - Impact resistant, dimensionally stable, bridges cracks, resistant to abrasion
 - Paintable individually
 - Rot resistant
 - Pre-pigmented
 - Free of PVC, plasticizers and solvents
- Certificates**
- Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 13501-1 (B.-s1, d0)
 - Oeko Tex® Standard 100
 - Contains no allergenic substances
 - A+ (VOC)

Roll size and packaging

Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
65000 060	1,00 x 25,00 m	45 g/m ²	20 rolls	80 rolls
65000 080	1,00 x 50,00 m	45 g/m ²	8 rolls	32 rolls
65011 080	1,00 x 50,00 m	130 g/m ²	6 rolls	24 rolls
65012 080	1,00 x 50,00 m	195 g/m ²	6 rolls	24 rolls
65020 080	1,00 x 50,00 m	130 g/m ²	6 rolls	24 rolls
65030 080	1,00 x 50,00 m	130 g/m ²	6 rolls	24 rolls
65045 080	1,00 x 50,00 m	45 g/m ²	8 rolls	32 rolls

10/2025



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical
data sheet

LECO
so simple. so good.

LECO Minerals

Instructions of use

- First step** Please check product prior to hanging. Irregularities in material are characteristic for this product and do not justify a complaint. Complaints after processing cannot be considered.
- Wall surface** The wall surface must be dry, clean, evenly coloured and absorbent. Old wallcoverings and non-adhesive coatings have to be removed. Cracks, joints and irregularities must be filled and smoothed. The wall has to be evenly absorbent. If necessary, treat prior to hanging.
- Hanging** Use the glass fibre adhesive LECOLLE Universal.
- Cut wallpaper length to according height incl. 5 - 10 cm extra material. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Overlap and double cut (article 65000) or butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.
- Painting** After drying, if desired or required, paint with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300.
- Note** The above information is only a general recommendation. We exclude any claims based on working conditions and wall constructions over which we have no influence. In case of doubt, please check.

10/2025



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)