



Technical
data sheet



LECOVER

Product description

- Material** LECOVER is a covering, heavy-duty glass veil.
- Use** By simply applying LECOVER Universal wallpaper, light to medium glass fabric structures and plaster (up to 3 mm) can be covered in a single step and the wall can be completely smoothed. Particularly suitable for commercial properties, as there is no need for time-consuming filling and work can be carried out efficiently.
- Properties**
- Covers light to medium structures in a single step
 - Bridges cracks
 - Quick to a smooth wall:
 - no filling
 - no sanding
 - dust free
 - no noise
 - up to 75 % faster*
 - Ideal as a wall liner and/or paint foundation
- Certificates**
- Complies with CE DIN EN 15102
 - Flame retardant in accordance with DIN EN 13501-1 (A2 - s1, d0)
 - Oeko Tex® Standard 100
 - Contains no allergenic substances
 - A (VOC)
 - sd value: The water vapour permeability according to DIN EN ISO 12572 C corresponds to a diffusion-equivalent air layer thickness of 0.02 m.

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	66000 060	1,00 x 25,00 m	375 g/m ²	8 Rolls	32 Rolls

*Compared to the classical plaster filling technique.

09/2025



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Technical
data sheet



LECOVER

Instructions of use

- First step** Please check product prior to hanging. Claims after usage will not be accepted.
- Wall surface** The substrate must be dry. Treat highly absorbent substrates with a deep primer. Non-absorbent or sealed substrates require a bonding coat with an adhesive primer. This is the case, for example, if the substrate to be covered is glass fabric coated with latex paint. LECOVER is bonded after the adhesive primer has dried.
- Hanging** Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.
- Cut wallpaper strips, adding 5-10 cm to allow for the top and bottom edges. Apply paste directly to the surface, lay the cut strips on top and press down with a wallpaper scraper/roller to remove any bubbles. Glue subsequent strips edge to edge and cut off any excess. Remove any excess paste immediately with a damp cloth or sponge.
- Painting** Once dry, the wallcovering can be wallpapered or painted with an adequate paint like dispersion, latex or acrylic paint according to DIN EN 13300.
- Note** The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt, we recommend conducting your own tests.

09/2025



STANDARD
100
DIN EN ISO 14184
Hohenstein HTTI



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)